

# A6&Q7 KEY CODER USER MANUAL

Connect the tool to the OBD of the Car.



PICTURE 1

Press OK to enter the main menu, Menu 1 is for OEM key and remote adaption, Menu 2 is for OEM remote adaption., Menu3 is for dealer's key.



**PICTURE 2**

Press OK to enter Menu 1 (key and remote adaption).



**PICTURE 3**

**Put the OEM key in the transponder adapter vertically.**



**PICTURE 4**

**Press OK to continue.**

*www.smelecom.com*

If the Key is blank, press OK to write the key, or press ESC to enter the process of adaption.



PICTURE 4

The next step is remote adaption.

[www.smelecom.com](http://www.smelecom.com)

**Put the OEM KEY in the transponder adapter horizontally.**



**PICTURE 5**

[www.smelecom.com](http://www.smelecom.com)



**PICTURE 6**

**Press OK to continue, please wait patiently.**



**PICTURE 7**

**Done.**



**PICTURE 8**

**If the key and remote all work well, all work is done.**

*www.smelecom.com*

If the remote doesn't work, go to Menu 2 to make the remote adaption.



PICTURE 9

Press OK to enter.



PICTURE 10

**Put the OEM KEY in the transponder adapter horizontally.**



**PICTURE 11**

*www.smelecom.com*



**PICTURE 12**

**Press OK to continue.**



**PICTURE 13**

**All work is done.**

If customer has dealer's key in hand , please choose Menu 3.



PICTURE 14

Press OK to enter



PICTURE 15

**Put the key in the transponder adapter.**



**PICTURE 16**

**Press OK to continue.**



**PICTURE 17**



**PICTURE 18**

**All work is done.**



**PICTURE 19**